



CE RAL 220 230V EVG 50Hz IP 20

LIDER A

reflektor / spotlight

Charakterystyka:

reflektor typu shoplight LED, do montażu na szynoprzewodzie

Opis techniczny:


obudowa i uchwyt reflektora wykonane z odlewu aluminiowego, malowane proszkowo w kolorze czarnym, białym lub szarym, odbłyśnik

Montaż:

na szynoprzewodzie

Zastosowanie:

obiekty handlowe, biurowe, pomieszczenia reprezentacyjne, galerie, muzea, salony samochodowe

type	product	kolor/colour	(Ra)		temperatura barwowa/colour temperature						kął świecenia/beam angle				max moc oprawy/ maximum power	max strumień oprawy/ maximum lumen output
			>80	>90	2500K	2700K	3000K	3500K	4000K	5000K	12°	22°	45°	64°		
Reflector	LIDER A	□ ■ ■	8	9	25	27	30	35	40	50	12	22	45	64	max 33W	max 4014lm
R	LA	WH GY BK	8	9	25	27	30	35	40	50	12	22	45	64		
akcesoria/accessories			szyba/glass		mleczna/opal		mrożona/frozen									
			1		2		3									

przykład oznaczenia zamawianego produktu/example code: **RLAOWH84045C3609501 - 1**



Characteristics:

shop-light lamp LED, assembled on the bus-duct

Technical description:

fitting and handle of the lamp made from aluminium casting pulverised in black, white or grey colour, reflecting element

Mounting:

on the bus-duct

Application:

commercial and office facilities, elegant halls, galleries, museum, car showrooms